

The AI is a single key access interlock ideal for use on hinged doors. The interlock has an open cavity design manufactured in either aluminium alloy/brass or stainless steel. Typical industries using the AI are food, chemical, pharmaceutical, mining, steel and power generation.


OPERATION

The Castell single key access interlocks are used in various applications to control part body access to hazardous areas.

AI single key access interlock (bolt trapped - key free)

1


Key is free, bolt is trapped.



While the key is free, the bolt of the AI is trapped in the mechanism. The door is locked.

2

Insert and turn key, then turn and release bolt.



By inserting and turning the key in the AI, the bolt is then free to be turned and released, which will trap the key in the lock.

3

Key is trapped, bolt is unlocked.



The key stays trapped while the bolt is released and the door is open.

USAGE

The AI Access Interlock should be used to allow safe access to potential hazardous and dangerous areas.

The AI Access Interlock should be used on part body access doors where the use of personal safety keys is not essential (to prevent accidental lock in).



The AI Access Interlock is not designed for security purposes, such as external access to a building.

No hazardous substances were used in the manufacture of this product. The product can be disposed of in standard waste.

INSTALLATION

The housing of the AI access interlock should normally be mounted on the static frame of the guard and the bolt to the sliding or hinged door using suitable fasteners. Fixed bolt bracket is highly tolerant to misaligned guards and should be fitted with suitable fasteners. Please refer to the drawing on page 4 for mounting details for the housing and bolt. The AI interlocks are available in Hand 1 and Hand 2 version suitable for left or right hinged doors, respectively. Anti vibration pads should be used on machines that generate a high level of vibration.



IMPORTANT: The AI Access Interlock should be mounted on the guard using anti-tamper fasteners to prevent unauthorised removal.



You must use M6 anti-tamper stainless steel screws secured using threadlock set to a torque of 5N/M.



Alignment limits of 0.5mm must be set in all planes. Angular displacement $\pm 1^\circ$ between lock and bolt.



The AI Access Interlock must be installed by a competent and qualified person who has read and understood these instructions. Please retain this document in your technical file.



The manufacturer should be consulted when use in a corrosive environment is planned.



Use middle strength threadlock on all four switch lid fixing screws and tighten to a torque of 5 N/M to retain IP65 rating.

MAINTENANCE

Periodic visual checks should be carried out by the site manager/safety officer.

Do not lubricate lock barrel with oil or grease, use CK Dry Powder Graphite if necessary.



The interlock must be inspected every 6 months. Safety checks should include ensuring the keys and lock bolt can only be removed in the correct safety operating conditions (see page 1).



In case of defects being detected please contact your nearest Castell Support Department for further actions. Please see Contact section for contact details.

AI

Single Key Access Interlock



TECHNICAL DATA


	AI Single Key Access Interlock
Temperature rating	Minimum: -40°C [-40°F] ice free for Q & FS lock type
	Maximum: 107°C [224.6°F] for Q lock type/140°C [284°F] for FS lock type
Type of mounting	Surface mount using M6 stainless steel anti-tamper fasteners
Weight	Brass: 0.8 kg
	Stainless steel: 1.0 kg
Material	Aluminium alloy/brass or stainless steel
Operation	Suitable for 1,000,000 operations.
B10d	1,250,000
Retention force	3.4 KN
Shock & vibration	In accordance with BS EN 50155 & IEC 61373
PL rating	PLd

APPLICATION

A typical application of the AI Single Key Access Interlock is machine guarding with part body access.

The AI safety component is used as part of an integrated safety system, which ensures a machine is shut down, before access to the hazardous area is allowed.

This system involves a KS key switch that breaks the machine safety circuit, when the key is removed. The key may then be inserted into the AI Access Interlock to enable access to the machine. The machine cannot be restarted until the door is closed, the bolt is replaced and the key is then removed and returned to the KS key switch.




DRAWING


Dimensions: in mm

Note: For safe mounting, use security screws

AI, Hand 2



Bolt Chain (Optional)



**NOTES:**



- 1) Bolt complete with D-Shackle
 - 2) Chain 5 x 18 SS
- Chain length to be defined by customer

ORDER INFORMATION

	Component type	1	2	3	4
Part number	AI				
Example	AI	FS	AL	1	ABC


1	Lock portion type	FS ⁽¹⁾ / Q ⁽¹⁾
2	Material	AL = Aluminium alloy/brass S = Stainless steel
3	Handing	1 = left hinged door (bolt enters left) ⁽²⁾ 2 = right hinged door (bolt enters right) ⁽²⁾
4	Lock portion symbol	FS ⁽¹⁾ up to 3 characters / Q ⁽¹⁾ up to 6 characters

(1)	FS - Lock type Up to 3 characters 	Q - Lock type Up to 6 characters 
-----	---	--

(2)	Handing <div> 1  </div> <div> 2  </div>
-----	--

Special construction available upon enquiry

ACCESSORIES

	Product Flip Cap	Part number FLIP-S
--	----------------------------	------------------------------

Castell Safety International

The Castell Building, 217 Kingsbury Road, London, NW9 9PQ, UK
 Tel: +44 (0)20 8200 1200 Email: sales@castell.com

5 of 5

While every effort has been made to ensure the accuracy of the information provided, no liability can be taken for any errors or omission. Sentric Safety Group reserves the right to alter specifications and introduce improvements without prior notice.

U-AI-01-E Issue 6 (05-25)