

Castell Safety International Ltd The Castell Building, 217 Kingsbury Road, London, NWg 9PQ, UK

> +44 (0)20 8200 1200 sales@castell.com

In compliance with:

CEN ISO 13849-1:2023

Safety of machinery, safety related parts of control systems

Part 1: general principles of design

MTTFd Olympus Series

B10d rating based on the calculated assumptions below is:-

= 5,000,000 cycles

Calculation data assumptions (CEN ISO 13849-1:2015. Annex C):

= Performance Level e (CEN ISO 13849-1. Table 2)

■ Safety Integrity Level 3 (CEN ISO 13849-1. Table 3)

■ MTTFd denotation HIGH (CEN ISO 13849-1. Table 4)

tcycle, mean time between two successive cycles 3600 seconds (1 cycle per hour)

hop, mean operation in hours per day 1 shift x 8 hours.

dop, mean operation in days per year 220 days.

 $nop = (dop \times hop \times 3600) / tcycle$ 1760 mean annual operations

B10d no. cycles until 10% of components fail dangerously 5,000,000 cycles

 $MTTFd = B10d / (0.1 \times nop)$ 28,409 years

 $\lambda d = (0.1 \text{ x nop}) / (B10d \text{ x } 220 \text{ x } 8)$ 4.02 E-09 per operating hour

Mechanical life 1,000,000 operations

Neal Partridge

Catalan -

Head of Compliance



